

Reolink Go PT Ultra

Smart 4K 4G PT Battery Camera

- 4K 8MP Ultra HD
- 4G LTE Network
- Color Night Vision



Specifications

Alarm	
Smart Alarm	PIR/person/vehicle/animal detection
PIR Detecting Distance	Adjustable up to 10m (33 ft)
PIR Detecting Angle	120° Horizontal
Audio Alert	Customized Audio Alerts
Recording	Motion-Triggered Recording
Other Alerts	Instant Email Alerts and Push Notifications
Power	
DC Power	USB Type-C port
Battery	21.6Wh Rechargeable Battery (Battery life varies based on settings, usage & temperature)
Solar	Reolink Solar Panel 2
Size & Weight	
Size	Φ98 x 122mm
Weight (Battery included)	496g

Video & Audio	
Image Sensor	1/2.7" CMOS Sensor
Video Resolution	3840 x 2160 (8 Megapixel)@15fps
Video Compression	H.265
Field of View	Fixed Lens, Horizontal: 90°, Vertical: 47° , Diagonal: 110°
Infrared Night Vision	Up to 10 Meters (33ft) (LED: 2pcs/1.2W/850nm)
Color Night Vision	Spotlight: 2pcs/2.4W/6500K
Audio	Two-Way Audio
Pan & Tilt	
Pan &Tilt	355° Pan, 140° Tilt
Preset Points	Supports 1 guard position & up to 32 preset positions
3G/4G	
Frequency Bands	<ul style="list-style-type: none"> • Europe Version: LTE FDD: B1/B3/B7/B8/B20/B28A WCDMA: B1/B8 • USA Version: LTE FDD: B2/B4/B5/B12/B13/B14/B66/B71 • Australia Version: LTE FDD: B1/B3/B5/B7/B8/B28 WCDMA: B1/B5/B8
Storage	
Local Storage	microSD Card (32GB included, max. 128GB)
Cloud Storage	Reolink Cloud (only available in some countries)
Smart Home	
Smart Home	Google Assistant
Working Environment	
Operating Temperature	-10 to 55° C (14° to 131° F)
Weather Resistance	IP64
Warranty	
Limited Warranty	

2-year limited warranty. For support, visit <https://support.reolink.com/hc/en-us/>

Gallery & Specs



1. Speaker
2. IR LEDs
3. Spotlights
4. Daylight Sensor
5. Lens
6. Status LED
7. PIR Motion Sensor
8. Built-in Microphone



1. Antenna
2. Battery LED
3. USB-C Port
4. Power Switch
5. Reset Hole
6. Nano SIM Card Slot
7. microSD Card Slot

www.reolink.com